

text for tenders

stainless steel roll-fitting for sliding doors.
astec b.410

wheel fitting made of stainless steel. fitting visible for floor guided sliding doors with door leaves made of glass, wood or mineral materials.

wheel fitting consisting of two flat wheel discs fitted on both sides of the door leaf at its lower edge. wheel fitting is available with an outer diameter of 120 mm or 160 mm.

the ball beared wheel discs are guided on a stainless steel track.

25 x 5 mm which can either be recessed flush into existing floor or can be mounted on the floor.

door load is transferred entirely into floor. u-profile ceiling guide prevents the door leaf from lifting out.

central ball bearing block is positioned in a cut-out of the door leaf and is tightly connected with one of the two wheel discs. the second wheel disc is connected via a central screw with this ball bearing block.

all bolted connections are designed invisibly.

all visible surfaces are finely processed and brushed matt.

manufacturer: astec gmbh, design fittings (www.astec-design.de)

system includes:

2 pcs stainless steel wheels with lateral cut-in(groove),
premounted, prepared for glass thicknesses 10/12 mm.
other thickness of door leaves according to specification.

1 pce floor guide made of stainless steel 25 x 5 mm,
length customised according to individual door width.

1 pce u-profile ceiling guide made of aluminium
lengths customised according to individual width of door

2 pcs door stoppers for fix positioning mounted into the ceiling guide.

with all fixing parts, complete paperwork.

from the astec accessories range are also available:

astec handles
astec knobs
astec flush pulls
astec locks